

TECHNICAL DATA SHEET

Performance Characteristics

Property	Typical Value	Test Method*
Particles and Fibers LPC: ≥0.5 μm Fibers: >100 μm	8.2 x 10 ⁶ particles/m ² 500 fibers/m ²	1, TM22 2, TM22
Nonvolatile Residue IPA extractant DIW extractant	0.02 g/m ² 0.01 g/m ²	1, TM1 1, TM1
Ions Sodium Potassium Chloride	0.05 ppm 0.07 ppm 0.02 ppm	1, TM18 1, TM18 1, TM18

Physical Characteristics

Property	Typical Value	Test Method*
Absorbency Sorbent capacity Sorbent rate	680 mL/m ² <1 second	1, TM20 1, TM20
Basis Weight	214 g/m ²	1, TM20

***Test Methods**

- 1 – “Evaluating Wiping Materials Used in Cleanroom and Other Controlled Environments,” IEST-RP-CC004.3, Institute for Environmental Sciences and Technology, Rolling Meadows, IL, 2004; www.iest.org.
- 2 – E2090-12, “Standard Test Method for Size-Differentiated Counting of Particles and Fibers Released from Cleanroom Wipers Using Optical and Scanning Electron Microscopy,” ASTM International, West Conshohocken, PA, 2012; www.astm.org.
- TM – Refers to Texwipe Test Method – available upon request. Contact Texwipe Customer Service at www.texwipe.com or info@texwipe.com for a copy.

Note: The data in this table represent typical analyses.

For sterile products:

- Gamma irradiated to a Sterility Assurance Level of 10⁻⁶ according to AAMI Guidelines.
- Certificates of Compliance, Analysis and Irradiation attached to each case.
- Sterile Validation Documentation available upon request.
- TX3252 – filled with USP grade IPA

Texwipe holds ISO 9001 and ISO 14001 registrations.

All Texwipe products conform to GHS classification for labeling (where applicable).

Shipping classification based on weight of inner package.

AlphaSorb[®] HC

Dry | Pre-Wetted | Sterile



TECHNICAL DATA SHEET



Products

Number	Description	Sterile	Packaging	Case
Dry Wipers – AlphaSorb® HC				
TX2409	9" x 9" (23 cm x 23 cm) dry		100 wipers/bag (2 inner bags of 50)	10 bags
TX2412	12" x 12" (31 cm x 31 cm) dry		100 wipers/bag (2 inner bags of 50)	6 bags
TX2418	18" x 18" (45 cm x 45 cm) dry		100 wipers/bag (2 inner bags of 50)	3 bags
Pre-Wetted Wipers – AlphaSat® with AlphaSorb® HC				
TX3252	12" x 12" (31 cm x 31 cm) pre-wetted with 70% IPA, sterile	●	25 wipers/flatpack	5 flatpacks

TECHNICAL DATA SHEET

Description

AlphaSorb® HC is made from 100% two-ply polyester with a cut edge, cleanroom laundered.

Available dry (AlphaSorb®HC) and sterile pre-wetted (AlphaSat® with AlphaSorb®HC).

Applications

- Wiping and cleaning surfaces, equipment and parts.
- Applying and removing lubricants, adhesives, residues and other solutions including disinfectants.
- Cleaning with solvents such as isopropyl alcohol (IPA), ethanol, acetone, and degreasers.
- Lining trays for holding, protecting, drying and storing of parts, equipment and devices.
- Appropriate for use with temperatures less than 400°F (205°C).

Industries

Aerospace	Animal Laboratory	Biologics
Cleanroom Design/Build	Compounding Pharmacies	Data Storage
Facilities Maintenance	Industrial	Laboratory
Medical Device	Microelectronics	Pharmaceutical
Printing/Graphics	Semiconductor	USP <797> / USP <800>

Features & Benefits

- Constructed from a double layer of polyester material creating a high absorbency wiper ideal for spill control, cleaning, and solution application.
- Cleanroom laundered providing low levels of ions and NVRs (non-volatile residues) particles.
- Designed for use on abrasive surfaces. This wiper will not easily snag or abrade releasing particles and fibers into the process or environment.
- Excellent chemical resistance for compatibility with a variety of solutions.
- AlphaSat® with AlphaSorb®HC is pre-wet with 70% IPA / 30% DIW for ease of use.
- Autoclave safe (dry wipers only).
- Individually lot coded for ease of traceability and quality control.

Cleanroom Environment

- ISO Class 4 – 8
- Class 10 – 100,000
- EU Grade A – D

Shelf Life

- Non-Sterile (Dry) – 5 years from date of manufacture
- Sterile (Pre-Wetted) – 3 years from the date of manufacture

Custom products available upon request.